



TWIN LOCK

Referencias disponibles / Available references

Distancia entre ejes / Distance between axes 85 mm				
	Referencia Reference	Aguja Backset (A)	Caja Case depth (B)	Entre ejes Interaxes (C)
TWIN LOCK	1320	20	34	85
TWIN LOCK	1325	25	39	85
TWIN LOCK	1330	30	44	85
TWIN LOCK	1335	35	49	85
TWIN LOCK	1340	40	54	85
TWIN LOCK	1350	50	61	85
TWIN LOCK	1360	60	71	85

Distancia entre ejes / Distance between axes 72 mm				
TWIN LOCK	1337	35	49	72
TWIN LOCK	1342	40	54	72
TWIN LOCK	1352	50	61	72
TWIN LOCK	1362	60	71	72

Mecanismos eléctricos / Electrical parts		
CIERRE/STRIKE	1300	Parte eléctrica / Electrical part 211 mm
CIERRE/STRIKE 24h	1302	24 Horas / 24 Hours. 100% DC
CIERRE/STRIKE	1305	Parte eléctrica / Electrical part 250 mm.

* Frontal de 250 mm, añadir una **L** a la referencia. p.e. 1320 L

* Front plate 250 mm, add a **L** to the reference. p.e.1320 L

* Opcional canto redondo / Round edge optional



Distancia separación entre partes 2,5 a 4 mm / Distance separation between parts 2,5 a 4 mm

El cilindro admite leva larga o corta / Short or long cam cylinder